



## C96 Tech Pro Series

Ultra-High Efficiency Two-Stage Gas Furnace

Visit [continentalheatingandcooling.com](http://continentalheatingandcooling.com) and see our Professional Support Center for the latest installation manuals, specification sheets and additional information.

# C96 Series Two-Stage Gas Furnace

Continental's two-stage furnace reduces temperature swings within your home, maintaining a consistent and comfortable setting. The C96 Series furnace will operate on low fire for greater efficiency and comfort for most of the heating season. On colder days, the furnace automatically switches to the second stage, producing more heat to satisfy demand. This effective two-stage system is like having two furnaces in one. With your Continental C96 Series furnace, you'll enjoy the winter seasons for years to come.

## Competitive Advantages

- One of the highest efficiency two-stage furnaces on the market at 96% AFUE
- Optional UV-C technology Furnace Kit to sanitize air, killing viruses and other airborne threats
- WHISPER QUIET™ operation with SILENTCORE™ technology
- Multi-position (upflow, horizontal and downflow) for versatile installations

## Features and Benefits

- 40,000 - 120,000 BTU models available
- Shortest 96%+ AFUE furnace on the market
- The C96 Series features a two-stage gas valve and variable speed energy efficient ECM motor
- T140 Aluminized Wrinkle Bent Primary Heat Exchanger Tubes
- Manufactured for natural gas
- Propane conversion kit available
- 29-4C Stainless Steel Heat Recovery Coil
- Premium Kyocera igniter

## SureView™ BURNER SYSTEM

Patented SureView™ burner system window allows a unique view of the flames in operation, a first in the industry.



## Modular DESIGN

The heat exchangers and blowers are removable allowing for easy installation and servicing- a feature that makes Continental Gas Furnaces the top choice.



**10 YEAR** | UNIT REPLACEMENT  
HEAT EXCHANGER LIMITED WARRANTY

**LIFE TIME** | HEAT EXCHANGER  
LIMITED WARRANTY

**10 YEAR** | PARTS  
LIMITED WARRANTY

Model	AFUE	Input High Fire	Input Low Fire	Cabinet Width (in)	Cabinet Depth (in)	Cabinet Height (in)	Clearances to Combustibles	Min. Vent Size (in)	Max. Vent Size (in)	Min. Vent Length (in)	Max. Vent Length (in)	Motor Size	AC Tonnages
WPV040T2AA-C	96%	40,000	24,000	17 1/2	29 1/2	34	0	1 1/2	2 1/2	15	75	1/3 hp	1 1/2, 2, 2 1/2
WPV060T3AA-C	96%	60,000	36,000	17 1/2	29 1/2	34	0	1 1/2	3	15	100	1/2 hp	1 1/2, 2, 2 1/2, 3
WPV080T3AA-C	96%	80,000	48,000	17 1/2	29 1/2	34	0	2	3	15	100	1/2 hp	1 1/2, 2, 2 1/2, 3
WPV080T4BA-C	96%	80,000	48,000	22 1/2	29 1/2	34	0	2	3	15	100	3/4 hp	2, 2 1/2, 3, 4
WPV0100T5BA-C	96%	100,000	60,000	22 1/2	29 1/2	34	0	2	3	15	100	1 hp	2.5, 3, 4, 5
WPV120T5BA-C	96%	120,000	72,000	22 1/2	29 1/2	34	0	3	3	15	100	1 hp	2.5, 3, 4, 5

- 103 Miller Drive, Crittenden, Kentucky, USA 41030
- 24 Napoleon Road, Barrie, Ontario, Canada L4M 0G8
- 7200 Trans Canada Highway, Montreal, Quebec, Canada H4T 1A3

Tel: 1-866-820-8686  
continentalheatingandcooling.com

Printed in Canada  
Effective: June 1, 2021  
v21-09-01



ADBC3-C96